

Bovie DERM 942

High Frequency Desiccator



The DERM 942 and it's patent pending handpiece are designed and engineered to be the most reliable and durable desiccator available today. The unit's life is prolonged by incorporating the latest in chip technology and reducing the number of internal parts, thereby generating less internal heat.

40 watt high frequency desiccator

Adjustable in 1/10th watt increments in the first 10 watts, in monopolar and bipolar

More accurate power with Universal Power Control 100-240 VAC

Less to do and less to buy makes this the most cost effective and user friendly unit on the market

The Bovie DERM 942 is a ground reference unit which means no grounding pad is required.



BOVIE® 942 HIGH FREQUENCY DESICCATOR







A804, A805, A806, A807, A806DE, A807DE

STANDARD EQUIPMENT

A942 (1) electrosurgical generator,

A902 (1) 3-Button Autoclavable Handpiece

A804 (5) non-sterile sharp dermal tips

A805 (2) sterile sharp dermal tips

A806 (5) non-sterile blunt dermal tips

A807 (2) sterile blunt dermal tips

A806DE (2) non-sterile DERM-Elite[™] Premium blunt dermal tips

A807DE (2) sterile DERM-Elite Premium blunt dermal tips

A910ST (2) sterile disposable handpiece sheath

A910 (2) non-sterile disposable handpiece sheath

A837 (1) wall mount kit

110 VAC Hospital-grade power cord*

User's guide (MC-55-239-001)*





A837



A910ST



A910

COMPLEMENTARY PRODUCTS †



A813
Table Top Stand †



A803 Footswitch †



A827V Forcep Cable †



A824 Reusable Bipolar Forceps †



ES20 Ball Electrode †



ES02 Needle Electrode †



A808-T Top Tray for A812 Stand †





[†] Sold Separately

PRODUCT SPECIFICATIONS

DIMENSIONS

Height: 188 mm (7.40 in.) Width: 228 mm (8.98 in.) Depth: 105 mm (4.13 in.) Weight: < 2.26 kg (< 5 lbs.)

OUTPUT POWER

To 40 watts (0-10 watts in 1/10th watt increments on both monopolar and bipolar)

OUTPUT FREQUENCY

328-492kHz

LINE VOLTAGE

A942: 100-240 VAC

LINE FREQUENCY

50 - 60Hz

WARRANTY

Four Years

