



SMOKE EVACUATION FOR THE OFFICE AND SURGERY CENTER



PROCEDURE SAFETY

AORN recommends the use of smoke evacuation systems during any medical procedure producing surgical smoke.

REDUCED RISK

500,000 healthcare professionals are exposed to surgical smoke proven to carry viruses, CO, and other chemical and biological hazards. The Smoke Shark II minimizes exposure to these toxic smoke plumes during electrosurgery, laser, and harmonic scalpel procedures.

COST EFFECTIVE

The Extended-Life Filter (SF35) offers up to 35 hours performance reducing procedure cost by 38%(+/-) when used at the lowest setting.

INCREASED EFFICIENCY

The Smoke Shark II Smoke Evacuator is compatible with most electrosurgical generators. The unit operates in conjunction with the optional Bovie Remote Activation Switch (SERS2) for maximized filter life and surgical efficiency.


MODERN DESIGN

A light-weight, ultra-quiet and compact design allowing for simplified operation, storage, and portability.

RELIABLE

The Smoke Shark II Smoke Evacuator includes a standard two (2) year manufacturer warranty.

STANDARD SETUP



| | | | |
|---|---|--|---|
| Long-Life 35-hr Filter | Pneumatic Footswitch | Smoke Evacuator Pencil Adapter with 6' Tube* | Remote Switch Activator* |
|  |  |  |  |
| SF35 (included) | FSSEP (included) | SEPAT | SERS2 |

* sold separately

Customize your Smoke Shark™ for a variety of applications by choosing from the accessories below:

| | | | | |
|---|---|--|---|---|
| 6' Tube (non-sterile) | 6' Tube with Wand & Tip (non-sterile) | 6' Tubing for ValleyLab® & IEC Pencil (sterile) | Laser-Resistant Wand (non-sterile) | Reducer Fitting |
|  |  |  |  |  |
| 786† | SETW† | SEVL | SELW | SERF† |

† Also available packed sterile

| Disposable Suction Coagulators | |
|---|--|
| Handswitch Activated | Footswitch Activated |
|  |  |
| SCH08‡ | SCF08‡ |

‡ Other sizes available



OTHER OPTIONAL ACCESSORIES

TECHNICAL SPECIFICATIONS

Smoke Shark II Technical Specifications...

| Dimensions: | Line Voltage: | Line Frequency: | Noise Level, dBA: |
|---|--|-----------------|--------------------|
| Height 15.2 cm (6 in.) Width 27.9 cm (11 in.) Depth 39.4 cm (15.5 in.) Weight 4.3 kgs (10 lbs) | SE02: 100/120 VAC SE02-220: 240 VAC | 50 - 60 Hz | 55.0 dBA (Maximum) |
| Warranty: limited two (2) year on unit only | | | |

The Smoke Shark II meets U.S. and International Standards.