

Mobile operating table with electrohydraulically driven longitudinal sliding movement Medifa 601120



Electro-hydraulic functions

- Height adjustment 690 -1050 mm
- Trendelenburg/ anti-trendelenburg -30° / +30°
- Lateral tilt -20° / +20°
- Lower backrest adjustment -40° / +70
- Lengthwise sliding 300 mm
- Flexion
- Fifth wheel
- Simultaneous levelling
- Central brake

Further information

- Table length (incl. head and leg rest) 2080 mm
- Table width 540 mm
- Table width incl. side guards 600 mm
- Maximum permissible total load 454 kg
- Weight of the table approx. 200 kg
- Power supply 110 V or 220 V / 50-60 Hz

Features

Hight ajustement	electrohydraulic
Flex/ reflex function	✓
Simultaneous level system (zero position)	✓
Reverse mode	✓
Mobile	Centrally braked castors
Attachment rails	Lateral rails for attaching accessories, stainless steel, 25 x 10 mm
5th castor	✓
Radiotranslucent	✓
Upholstery	Viscoelastic / electrically conductive / removable
Safe working load	454 kg
Type of series	Medifa 6000

Dimensions

Length	69 - 105 cm
Width	54 cm
Width including side rails	60 cm
Adjustable height	69 - 105 cm
Lateral tilt (lateral tilt)	-20°/+20 °
Trendelenburg tilt	-30°/+30 °
Tilt lower backrest	-40°/+70
Max Longitudinal sliding	30
Weight	200 kg