

Electromechanical mobile operating table Medifa 504320



Electromechanical functions

- Height adjustment 780 - 1080 mm
- Trendelenburg -30° / +25°
- Lateral tilting -20° / +20°
- Backrest adjustment -40° / +70
- Lengthwise sliding 285 mm (only applies to 504325)
- Flexion
- Memory (3 positions)
- Simultaneous levelling

Further information

- Table length (incl. head and leg rest) 2080 mm
- Table width 540 mm
- Table width incl. side guards 600 mm
- Maximum permissible total load 250 kg
- Weight of the table approx. 175 kg
- Power supply 110 V or 220 V / 50-60 Hz

Features

Hight ajustement	electromechanical
Flex/ reflex function	✓
Memory functions	3
Simultaneous level system (zero position)	✓
Attachment rails	lateral rails for attaching accessories, stainless steel, 25 x 10 mm
Hand control	✓
Operating unit on the table column	✓
Mobile	four double swivel castors ø 125 mm with central brake, electrically conductive, two castors with direction stability
Upholstery	visco-elastic / electrically conductive / removable
Power supply	110 V of 220 V / 50-60 Hz
Safe working load	250 kg

Dimensions

Length	including head and leg rest 208 cm
Width	54 cm
Width including side rails	60 cm
Adjustable height	78 - 108 cm
Trendelenburg tilt	-30°/+25 °
Lateral tilt (lateral tilt)	-20°/+20° °
Back tilt	-40°/+70 °
Weight	175 kg